

External Transparent Straight Connector

Direct Buried / Push Fit

General Data

Item	Straight Connector
Description	A straight connector which is suitable for connecting a wide range of external duct, providing protection against gas and water up to 15 bar. The HellermannTyton range of straight connectors are reusable, each connector is fitted with a locking ring which is quick and simple to fit/remove.

Product Specification

Material	Polyamide PA				
Part Code		Diameter	Length	Unit	Pack Size
Dimensions	DSM-7MM-EXT	13	32	mm	50
	DSM-8MM-EXT	15	37		
	DSM-10MM-EXT	18	42		
	DSM-12MM-EXT	22	46		
	DSM-14MM-EXT	24	47		25
	DSM-16MM-EXT	26	48		
	DSM-18MM-EXT	29	49		
	DSM-20MM-EXT	33	56		
DSM-25MM-EXT	40	61			
Fire Behaviour (DIN EN 13501-1)	E-d2				
Pressure	0.5 (permanent gas and watertight)			Bar	
	15 / 30			Bar / Min	
Burst Pressure	Min. 30			Bar	
Tensile Strength	DSM-7MM-EXT	Min. 200		N	
	DSM-8MM-EXT	Min. 300			
	DSM-10MM-EXT	Min. 400			
	DSM-12MM-EXT	Min. 450			
	DSM-14MM-EXT	Min. 500			
	DSM-16MM-EXT	Min. 550			
	DSM-18MM-EXT	Min. 550			
	DSM-20MM-EXT	Min. 600			
DSM-25MM-EXT	Min. 650				