



Easy Clip Category 5e UTP

Single Outlet

Application/Product Description

Easy Clip Category 5e single outlets are designed to support Ethernet 10BASE-T, 100BASE-T (Fast Ethernet), 155 Mb/s ATM, Token Ring 4/16, voice/data systems and Voice over Internet Protocol (VoIP) systems running over a Category 5e cabling system and is backwards compatible with existing Category 5 and voice network infrastructures.



Easy Clip Category 5e UTP Single Outlet

Technical Data


Specification	Category 5e		
Conformance	<ul style="list-style-type: none"> • ISO 11801:2002 (inc. Amend. A1 & A2) • BS EN 50173 • ANSI/TIA/EIA 568-C.2 		
Wiring Specification	568A/B		
Dimensions (mm)	H	W	D
	50.0	25.0	34.0
Weight (g)	18		
Outlet Style	RJ45		
RJ45 Jack Life	Minimum Insertions 1000		
Punch Down Blocks	IDC		
IDC Life	Minimum 50 re-terminations		
Wire Gauge	22-24 AWG (Maximum of 2 wires per contact).		

Material			
Modular Jack Housing	ABS		
Housing Colour	White	Black	
Contacts	Phosphor Bronze Nickel Plated with Selective Gold		


Performance Characteristics

Frequency (MHz)		1	10	100
Insertion Loss	Spec	3.0	6.2	21.0
	Typical	1.9	5.6	18.2
NEXT (dB)	Spec	60.0	48.5	32.3
	Typical	83.8	69.3	49.2
ACR-N (dB)	Spec	57.0	42.3	11.3
	Typical	81.9	63.7	30.9
Return Loss (dB)	Spec	19.0	19.0	12.0
	Typical	29.1	33.7	31.9
PS NEXT (dB)	Spec	57.0	45.5	29.3
	Typical	78.9	63.4	43.4
PS ACR-N (dB)	Spec	54.0	39.3	8.3
	Typical	77.0	57.9	25.2
ACR-F (dB)	Spec	58.6	38.6	18.6
	Typical	73.8	53.9	37.0
PS ACR-F (dB)	Spec	55.6	35.6	15.6
	Typical	67.8	47.9	31.9


*Typical values are for permanent link tests when using the complete HellermannTyton Data System.




Technical Diagrams



Front view



Side view



Top view