HellermannTyton



Technical Data Sheet

Fibre Cleaning Liquid - Non-Combustable/Aqueous HT-FPC-LQNCA/100ML and HT-FPC-LQNCA/1LTR

Application/Product Description

Fibre Cleaning Liquid, available in 100ml or 1litre bottles, contains a nonflammable, water-based cleaning solution that quickly and safely cleans the end face of fibre optic connectors, splices and ribbons. It also dissipates static charge, which prevents attracting airborne contamination that cling to the end face surface.

The cleaning formulation has low odour, is plastic safe, and residue free. Because it is water-based, it has the environmental benefits of low VOC and GWP (Global Warming Potential).

This non-pressurized container can be easily and safely transported. For best results, use with the End Face Dry Wipe Cube Platform or End Face Click Cleaner Tool and the Combination Cleaning process.

Features and Benefits

- Nonflammable aqueous cleaner
- Removes a broad range of soils dust, oils, soils, complex soils, salts
 and other contaminants
- Residue free, low VOC, low global warming potential (GWP)
- Portable and easily transportable
- Cleans connectors with End Face Dry Wipe Cube Platform or with End Face Click Cleaner Tool
- Dissipates static charge which can attract airborne contaminants
- Plastic safe and compatible for all fibre optic connectors

Typical Applications

- Connector end face cleaning
- Cleaning fibre and splice trays pre-splice
- Cleans tools and meters
- · Cleans cables
- · All repair and maintenance spot cleaning

Compatibility

Fibre Cleaning Liquid is compatible with most materials used in telecommunications. As with any solvent, compatibility with substrate should be determined on a non-critical area prior to use.

Material	Compatibility	Material	Compatibility
ABS	Excellent	Noryl®	Excellent
Buna-N	Excellent	Nylon 66™	Excellent
EPDM	Excellent	Cross-Linked PE	Excellent
Graphite	Excellent	Polypropylene	Excellent
HDPE	Excellent	Polystyrene	Excellent
Kynar™	Excellent	PVC	Excellent
LDPE	Excellent	Silicone Rubber	Excellent
Lexan™	Excellent	Teflon	Excellent
Neoprene	Excellent	Viton	Excellent



HT-FPC-LQNCA/100ML and HT-FPC-LQNCA/1LTR.

Product Data And Physical Properties

Appearance	Clear, colourless liquid		
Odour	Mild		
Solubility in Water	100%		
Specific Gravity	0.98 @ 23.9°C (water = 1@77°F)		
Evaporation Rate	>1 (butyl acetate = 1)		
Boiling Point	>93°C		
Flash Point (TCC)	None		
VOC* Content			
CARB	7%		
SCAQMD	85 g/L		
Federal	7%		
Shelf life	5 years		
RoHS Compliant	Yes		

* ODP, HCFC-225, Chlorinated Solvent, VOC, HFC, and nPB percentages show n are the content by weight. Volatile Organic Compound (VOC) information is calculated on a weight basis using the VOC definition of California Air Resources Board (CARB) Consumer Product Regulations, South Coast Air Quality Management District (SCAQMD) Rule 102 and the Federal definition published in 40 CFR 51.100(s).

Environmental Impact Data

ODP	0%
HCFC 225	0%
HFC	0%
CL Solv.	0%
nPB	0%

CFC, HCFC-225, HCFC-141b, VOC, HFC, and nPB percentages shown are the content by weight.

HellermannTyton