



External End Cap

Direct Buried / Push Fit

General Data

Item	End Cap
Description	An end cap which is suitable for use with a wide range of ducts providing protection against gas and water ingress up to 5. The HellermannTyton range of end caps are reusable, each end cap is fitted with a locking ring which is quick and simple to fit/remove.

Product Specification

Material	Polyamide PA				
Part Code		Diameter	Length	Unit	Pack Size
Dimensions	ES-7MM-EXT	13	17	mm	50
	ES-8MM-EXT	15	20		
	ES-10MM-EXT	18	22		
	ES-12MM-EXT	21	25		25
	ES-14MM-EXT	23	25		
	ES-16MM-EXT	25	25		
	ES-20MM-EXT	32	30		
Fire Behavior (DIN EN 13501-1)	E – d2				
Pressure	0.5 (permanent gas and watertight)			Bar	
	15 / 30			Bar / Min	
Burst Pressure	Min. 30			Bar	
Tensile Strength	ES-7MM-EXT	Min. 200			N
	ES-8MM-EXT	Min. 300			
	ES-10MM-EXT	Min. 400			
	ES-12MM-EXT	Min. 450			
	ES-14MM-EXT	Min. 500			
	ES-16MM-EXT	Min. 550			
	ES-20MM-EXT	Min. 600			