

External Transparent Reducer

Direct Buried / Push Fit

General Data

Item	Reducer
Description	A reducer which is suitable for the gas and watertight connection of duct with the same internal diameter up to 15 bar. The range of RSM reducers are reusable, each reducer is fitted with a locking ring which is quick and simple to fit/remove.

Product Specification

Material	Polycarbonate PC				
Part Code		Diameter	Length	Unit	Pack Size
Dimensions	RSM-7/5MM-EXT	13	34	mm	25
	RSM-8/7MM-EXT	15	37		
	RSM-10/7MM-EXT	18	35		
	RSM-12/10MM-EXT	22	46		
	RSM-14/12MM-EXT	24	47		
RSM-16/14MM-EXT	26	48			
Fire Behavior (DIN EN 13501-1)	E -d2				
Pressure	0.5 (permanent gas and watertight)			Bar	
	15 / 30			Bar / Min	
Burst Pressure	Min. 30			Bar	
Tensile Strength	RSM-7/5MM-EXT	Min. 120		N	
	RSM-8/7MM-EXT	Min. 200			
	RSM-10/7MM-EXT	Min. 200			
	RSM-12/10MM-EXT	Min. 400			
	RSM-14/12MM-EXT	Min. 450			
	RSM-16/14MM-EXT	Min. 500			